



#### FUNCTIONAL SUMMARY

	IN	OUT
#	1, 1	2+1A
TYPE	USB Zigbee® Radio Module	2 Wire or 3 Wire
FORM	---	A or C, A for EOI

# MPG-3SC

## SPECIALTY DEVICES

# MPG-3SC WIRELESS METER PULSE GENERATOR

## DESCRIPTION

The MPG-3SC Wireless Meter Pulse Generator is SSI's third generation Zigbee Pulse Generator. It integrates AMI smart meters with legacy KYZ pulse metering. Using Zigbee® radio technology, the MPG-3SC receives usage data from the meter's HAN network, interprets power usage, and converts it into KYZ pulses. With the MPG-3SC, pulses are synthesized without having an actual KYZ output in the meter. By using the MPG-3SC, utilities can implement the new advanced AMI meters and still provide pulses to customers that may need them.



The MPG-3SC features integral Zigbee radio module and two KYZ pulse outputs, in a fiberglass NEMA 4X enclosure. As the MPG-3SC receives periodic data from utility's meter, the data is read and interpreted to obtain the current demand information. Accumulated energy is computed, and pulses are outputted according to a selected pulse value.

All system settings are accomplished through a USB programming port that provides for pulse value, meter multiplier, output mode, and pulse timing. The output is selectable as either Form A (2-Wire) or Form C (3-Wire) and operates in either the momentary or toggle mode, respectively. The momentary mode has six pulse width time settings: 25mS, 50mS, 100mS, 200mS or 500mS and 1000mS. The toggle mode toggles back and forth to the opposite state upon each new pulse being generated. There are two LED's, one red and one green, which show pulse output status.

The output pulse value is selectable from 1 to 99999 watt-hours per pulse. A meter multiplier of 1 to 99999 may be programmed into the MPG-3SC using the SSI Universal Programmer software.

A 30mS fixed minimum-off time delay prevents pulses from occurring too rapidly. Bright red, yellow and green LEDs monitor the system communications status and provide an easy and immediate visual system check without test equipment.

The Zigbee module must be paired or "provisioned" with the AMI meter with a HAN network radio, a process that is performed by the participating utility or on the utility's website. Once paired with the meter, the MPG-3SC will begin receiving information from the meter and generating pulses.

The MPG-3SC is compatible with Self-Contained or Instrument-rated electric meters. The MPG-3SC's USB programming port is used to enter the specified site's meter multiplier from 1 to 99999. In addition, the MPG-3SC can be configured for Normal mode (kWh delivered only) for unidirectional energy flow, or for Signed mode (kWh delivered and received) for bi-directional energy flow. The MPG-3 also supports End-Of-Interval capability with a Form A (2-wire) output for intervals over a wide range.



# MPG-3SC

SPECIALTY DEVICES

## MPG-3SC WIRELESS METER PULSE GENERATOR

### SPECIFICATIONS

#### ELECTRICAL

Power Input:	120, 208-277 VAC. Burden: 10 VA
Input:	Zigbee HAN Network with AMI meter
Output:	Two Form A (2-Wire) or Form C (3-wire) Solid State dry-contact outputs rated at 100mA at 120V, 800mW maximum, fused at .1A
Maximum Pulse Output Rate:	≈15 Pulses per second (Form C) ≈10 pulses per second (Form A)
Minimum Time between Output Pulses:	30ms
Form A Pulse Width:	25, 50, 100, 200, 500, 1000 mS
Output Pulse Values:	1-99999 Wh/pulse
End of Interval Output:	1 Form A (2-wire) output for EOI
Interval Lengths:	1, 5, 10, 15, 30, 60 minutes
Interval Pulse Widths:	50, 100, 250, 500, 1000, 2000, 5000, 10000mS

#### MECHANICAL

Mounting:	Any position
Size:	9.5' wide, 11.5' high, 4 3/8" deep
Weight:	7 pounds

#### TEMPERATURE

Temperature Range:	-38° C to +70° C, -38.4° F to +158° F
Humidity:	0 to 98% non-condensing

#### AVAILABLE OPTIONS

Input Voltages:	Contact factory
Enclosures:	NEMA 4X fiberglass raintight and dustproof enclosure available. 10.0" high, 8.0" wide, 4.0" deep, includes mounting plate